



**KOTEC CORP**

21-15 3-CHO CHAYAMADAI SAKAI-SHI OSAKA 590-0115 JP

Material Designation: **KG-10MRA**

Product Description: Polycarbonate (PC), designated "Carbotex, Kotex" furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.5	V-2	2	3	80	80	80	-	-
	3.0	V-0	1	0	80	80	80	-	-

**CTI: 3**    **IEC CTI (V): -**    **HVTR: 3**    **D495: -**    **IEC Ball Pressure (°C): -**

<b>Dielectric Strength (kV/mm): -</b>	<b>Volume Resistivity (10<sup>x</sup>ohm-cm): -</b>	<b>Dimensional Stability(%): -</b>
<b>ISO Tensile Strength (MPa): -</b>	<b>ISO Flexural Strength (MPa): -</b>	<b>ISO Heat Deflection (°C): -</b>
<b>ISO Tensile Impact (kJ/m<sup>2</sup>): -</b>	<b>ISO Izod Impact (kJ/m<sup>2</sup>): -</b>	<b>ISO Charpy Impact (kJ/m<sup>2</sup>): -</b>

Report Date: 9/1/1994

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.